


Technical Specifications (Slip Ring)	
Circuits	16 Circuits: 16x2A
Rating Voltage	0~240Vac/Vdc
Working Temperature	-20°C ~ +80°C
IP Grade	IP51
Working Speed	0~250 rpm
Contact Material	Precious Metal
Housing Material	Aluminum Alloy
Lead Wire Length	Rotor: 200mm / Stator: 200mm

“WE RESERVE ALL RIGHTS IN CONNECTION WITH THIS DOCUMENT AND IN THE SUBJECT MATTER REPRESENTED THEREIN. THE RECIPENT HEREBY ACKNOWLEDGES THESE RIGHTS AND SHALL NOT, WITHOUT OUR PRIOR PERMISSION IN WRITING, DISCLOSE OR DIVULGE THIS DOCUMENT IN WHOLE OR IN PART TO THE THIRD PARTIES OR USE IT FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS DELIVERED TO RECIPIENT.”

ANGULAR TOLERANCE: $\pm 0.5^\circ$
TOLERANCE:
>0.5 - 6 ± 0.1
>6 - 30 ± 0.2
>30 - 120 ± 0.3
>120 - 400 ± 0.5
>400 - 1000 ± 0.8
>1000 - 2000 ± 1.2
>2000 - 4000 ± 2.0

CUSTOMER:
APPLICATION:
PROJECTION:

	Slip Ring Outline Drawing		
	ZER-X1 HG-RSZS-17-S001		
ARTICLE NO:			
Designer: KHK	Date: 22.04.2024	Drawing No: 10083	Rev:1